

PRESENTATION BEFORE THE NTSB INVESTIGATIVE HEARING JAPAN AIRLINES, JA829J BOEING 787 BATTERY FIRE

PANEL 3: 787 BATTERY DESIGN VERIFICATION & VALIDATION


APRIL 24, 2013






Process & Roles: Qualification (GSYÚASA)












Collaboration: Qualification Test GSYÚASA



Collaboration: Qualification Test Report



Collaboration: Safety Assessment Process



Qualification Testing



| Test Category | Test Article | Test Name | Battery 1 | Battery 2 | Battery 3 | |
|--------------------------------------|-----------------|--|--------------|-----------------------|--------------|--|
| Functional Test (Electrical Test) | Battery | Discharge Test (APU, E-Brake, Constant Current) | $\sqrt{}$ | $\sqrt{}$ | $\sqrt{}$ | |
| | | Charge Test | \checkmark | $\sqrt{}$ | \checkmark | |
| Climatic Test | Battery | Temperature test (high and low) | $\sqrt{}$ | $\sqrt{}$ | $\sqrt{}$ | |
| | | Temperature variation test | $\sqrt{}$ | $\sqrt{1}$ | $\sqrt{1}$ | |
| | | Altitude test | $\sqrt{}$ | $\sqrt{}$ | $\sqrt{}$ | |
| | | Overpressure test | \checkmark | \checkmark | \checkmark | |
| | | Decompression test | \checkmark | — ² | \checkmark | |
| | | Humidity test | \checkmark | \checkmark | \checkmark | |
| Mechanical Test | Battery | Random vibration | \checkmark | \checkmark | \checkmark | |
| | | High power vibration | _3 | \checkmark | \checkmark | |
| | | Fan blade loss vibration | \checkmark | \checkmark | \checkmark | |
| | | Acceleration test | \checkmark | \checkmark | \checkmark | |
| | | Bench handling test | \checkmark | \checkmark | \checkmark | |
| | | Container shock test | $\sqrt{}$ | $\sqrt{}$ | \checkmark | |
| EMI/EMC Test | Battery | EMI/EMC tests in accordance with D6-16050-5 (including: audio frequency conducted emission, radio frequency conducted emission, audio frequency susceptibility, radio frequency susceptibility, transient susceptibility, lighting induced transient susceptibility, BMU function, electrostatic discharge susceptibility) | V | V | √ | |
| Abuse Test | Battery | Overcharge test | $\sqrt{}$ | $\sqrt{}$ | \checkmark | |
| | | High temperature storage test | \checkmark | $\sqrt{}$ | $\sqrt{}$ | |
| | | Under discharge test | $\sqrt{}$ | $\sqrt{}$ | $\sqrt{}$ | |
| | | External short circuit test | $\sqrt{}$ | $\sqrt{}$ | $\sqrt{}$ | |
| | | High impedance external short circuit test | _ | _ | $\sqrt{}$ | |
| Abuse Test | Cell | Crush Test | _ | | | |
| | | | | | | |

Note 1: Fewer cycles required for QT.

Note 2: Not required because the sealing designs for the battery box and cells were the same as Battery 1.

Note 3: Not applicable